


Planeo 4048

Geolam[®]
Architectural Eco-Technology

Hybrid Aluminum/WPC Architectural Elements

Datasheet



Thickness: 50 mm | 2 in

Width: 300 mm | 11 3/4 in

Section tolerances in mm: + 0.5 / - 2.0

Fire rating:

On request before order

Surfaces finish: sanded

Standard length: 3.00 m | 9 ft 10 in

Or order any length from:
2.45 m | 8 ft to 5.48 m | 18 ft

Weight: 4.80 kg/lm | 3.23 lb/ft

Secondary moment Ix (cm⁴): 31,707.34

Secondary moment Iy (cm⁴): 646,931.02

Section modulus Zx (cm³): 2,698.5

Section modulus Zy (cm³): 8,712.88

Core in anodized aluminum alloy:

A6063S-T5

Coefficient of Thermal Expansion:

(20-100°C) : 23.4 µm/m/°C

Modulus of Elasticity: 68.6 GPa

Tensile Strength: 186 Mpa min

Standard Colors - Minimum 1,800 ft for all colors:



Teak



Moleskin



Rosewood



Ebony

Non-Standard Colors - 90 day lead time - Minimum order quantities apply:



Ivory



Blackwood

Custom Colors Available for orders >6,000 sq. ft.

www.geolaminc.com
Toll free: 1-877-627-3530
info@geolaminc.com