


Soleo 6031

Geolam[®]
Architectural Eco-Technology

Hybrid Aluminum/WPC Architectural Elements

Datasheet



Thickness: 28 mm | 1 1/8 in

Width: 126 mm | 5 in

Section tolerances in mm: + 0.5 / - 2.0

Fire rating:

On request before order

Surfaces finish: sanded

Standard length: 3.00 m | 9 ft 10 in

Or order any length from:
2.45 m | 8 ft to 5.48 m | 18 ft

Weight: 1.75 kg/lm | 1.16 lb/ft

Secondary moment Ix (cm⁴): 5.3

Secondary moment Iy (cm⁴): 72.60

Section modulus Zx (cm³): 4.30

Section modulus Zy (cm³): 11.80

Core in anodized aluminum alloy:

A6063S-T5

Coefficient of Thermal Expansion:

(20-100°C) : 23.4 µm/m/°C

Modulus of Elasticity: 68.6 GPa

Tensile Strength: 186 Mpa min

Core cross section (mm²): 45.50

Standard Colors -  Teak and Rosewood stocked in the US, no minimum.
Minimum 1,000 ft for Moleskin and Ebony:



Teak



Moleskin



Rosewood



Ebony

Non-Standard Colors - 90 day lead time - Minimum order quantities apply:



Ivory



Blackwood

Custom Colors Available for orders >6,000 sq. ft.

www.geolaminc.com
Toll free: 1-877-627-3530
info@geolaminc.com