



Planeo 4048

Geolam[®]
Architectural Eco-Technology

Hybrid Aluminum/WPC Architectural Elements

Datasheet



*Technical information may change without warning.
Please ensure you that you reference our latest as shown on our website at www.geolaminc.com*

Thickness: 2 in | 50 mm
Width: 11 3/4 in | 300 mm
Section tolerances in mm: + 0.5 / - 2.0

Fire rating:
On request before order

Surfaces finish: Sanded

Profiles fastening and installation:
Check our website www.geolaminc.com

Standard length: 9 ft 10 in | 3.0 m

Or order custom lengths from:
7 ft to 27 ft | 2.15 m to 8.25 m

Weight: 3.23 lb/ft | 4.80 kg/m

Secondary moment I_x (cm⁴): 50.73

Secondary moment I_y (cm⁴): 1035.09

Section modulus Z_{+x} (cm³): 21.58

Section modulus Z_{-x} (cm³): 21.58

Section modulus Z_{+y} (cm³): 69.7

Section modulus Z_{-y} (cm³): 69.7

Core in anodized aluminum alloy:
A6063S-T5 Serie 6000

Coefficient of Thermal Expansion (20-100°C):
23.4 µm/m/°C

Modulus of Elasticity: 68.9 GPa

Max Tensile Strength: 186 Mpa

Carbon Footprint:
WPC : 1.54 kg CO₂ /Kg
Profile : 9.005 kg CO₂ /Kg

Sanding finish and/or shading may vary between runs

Standard Colors - Minimum 1,600 ft for all colors.



Teak



Moleskin



Rosewood



Ebony


Non-Standard Colors - 90 day lead time - Minimum order 5,000 ft.



Ivory




Blackwood



Bilinga

Custom Colors Available - Minimum order 10,000 ft.

www.geolaminc.com
Toll free: 1-877-627-3530
info@geolaminc.com



300.0 mm / 11 3/4" ^{+1.0}_{-3.0}

50.0 mm / 2" ^{+0.5}_{-1.5}

Technical specifications, dimensions in mm		Cross section coefficient Z+x (cm ³)		Wood hybrid system WHS	Type 1.0
Weight (kg/ml)	4.8	Cross section coefficient Z-x (cm ³)	2698.50	Planeo 4048	
Cross section, secondary moment Ix (cm ⁴)	31707.34	Cross section coefficient Z+y (cm ³)	8712.87		
Cross section, secondary moment Iy (cm ⁴)	646931.02	Cross section coefficient Z-y (cm ³)	8712.87		