



Planeo 4061

Geolam®
Architectural Eco-Technology

Hybrid Aluminum/WPC Architectural Elements

Datasheet



*Technical information may change without warning.
Please ensure you that you reference our latest as shown on our website at www.geolaminc.com*

Thickness: 4 in | 100 mm
Width: 11 3/4 in | 300 mm
Section tolerances in mm: + 0.5 / - 2.0

Fire rating:
On request before order

Surfaces finish: Sanded

Profiles fastening and installation:
Check our website www.geolaminc.com

Standard length: 9 ft 10 in | 3.0 m

Or order custom lengths from:
7 ft to 27 ft | 2.15 m to 8.25 m

Weight: 6.38 lb/ft | 9.50 kg/m

Secondary moment Ix (cm⁴): 378.86

Secondary moment Iy (cm⁴): 2010.35

Section modulus Z+x (cm³): 78.11

Section modulus Z-x (cm³): 78.11

Section modulus Z+y (cm³): 135.38

Section modulus Z-y (cm³): 135.38

Core in anodized aluminum alloy:
A6063S-T5 Serie 6000

Coefficient of Thermal Expansion (20-100°C):
23.4 µm/m/°C

Modulus of Elasticity: 68.9 GPa

Max Tensile Strength: 186 Mpa

Carbon Footprint:
WPC : 1.54 kg CO₂ /Kg
Profile : 9.005 kg CO₂ /Kg

Sanding finish and/or shading may vary between runs

Standard Colors - Minimum 1,600 ft for all colors.



Teak



Moleskin



Rosewood



Ebony


Non-Standard Colors - 90 day lead time - Minimum order 5,000 ft.



Ivory




Blackwood



Bilinga

Custom Colors Available - Minimum order 10,000 ft.

www.geolaminc.com
Toll free: 1-877-627-3530



Technical specifications, dimensions in mm		Cross section coefficient Z+x (cm ³)		78.11	Wood hybrid system WHS	Type 1.0
Weight (kg/ml)	9.5	Cross section coefficient Z-x (cm ³)	78.11		Planeo 4061	
Cross section, secondary moment Ix (cm ⁴)	378.86	Cross section coefficient Z+y (cm ³)	135.38			
Cross section, secondary moment Iy (cm ⁴)	2010.35	Cross section coefficient Z-y (cm ³)	135.38			