



Planeo 4062

Geolam[®]
Architectural Eco-Technology

Hybrid Aluminum/WPC Architectural Elements

Datasheet



*Technical information may change without warning.
Please ensure you that you reference our latest as shown on our website at www.geolaminc.com*

Thickness: 4 in | 30 mm
Width: 17 3/4 in | 435 mm
Section tolerances in mm: + 0.5 / - 2.0

Fire rating:
On request before order

Surfaces finish: Sanded

Profiles fastening and installation:
Check our website www.geolaminc.com

Standard length: 9 ft 10 in | 3.0 m

On order any length from:
7 ft to 27 ft | 2.15 m to 8.25 m

Weight: 9.54 lb/ft | 14.25 kg/m

Secondary moment I_x (cm⁴): 568.29

Secondary moment I_y (cm⁴): 6247.14

Section modulus Z_{+x} (cm³): 117.17

Section modulus Z_{-x} (cm³): 117.17

Section modulus Z_{+y} (cm³): 279.51

Section modulus Z_{-y} (cm³): 279.51

Core in anodized aluminum alloy:
A6063S-T5 Serie 6000

Coefficient of Thermal Expansion (20-100°C):
23.4 µm/m/°C

Modulus of Elasticity: 68.9 GPa

Max Tensile Strength: 186 Mpa

Carbon Footprint:
WPC : 1.54 kg CO₂ /Kg
Profile : 9.005 kg CO₂ /Kg

Sanding finish and/or shading may vary between runs

Standard Colors - Minimum 1,600 ft for all colors.



Teak



Moleskin



Rosewood



Ebony


Non-Standard Colors - 90 day lead time - Minimum order 5,000 ft.



Ivory




Blackwood



Bilinga

Custom Colors Available - Minimum order 10,000 ft.

www.geolaminc.com
Toll free: 1-877-627-3530



Technical specifications, dimensions in mm		Cross section coefficient Z+x (cm ³)		117.17	Wood hybrid system WHS	Type 1.0
Weight (kg/ml)	14.25	Cross section coefficient Z-x (cm ³)		117.17	Planeo 4062	 www.geolaminc.com
Cross section, secondary moment Ix (cm ⁴)	568.29	Cross section coefficient Z+y (cm ³)		279.51		
Cross section, secondary moment Iy (cm ⁴)	6247.14	Cross section coefficient Z-y (cm ³)		279.51		