



Soleo 6008

Geolam[®]
Architectural Eco-Technology

Hybrid Aluminum/WPC Architectural Elements

Datasheet



*Technical information may change without warning.
Please ensure you that you reference our latest as shown on our website at www.geolaminc.com*

Thickness: 1 1/4 in | 30 mm
Width: 2 in | 50 mm
Section tolerances in mm: + 0.5 / - 2.0

Fire rating:
On request before order

Surfaces finish: Sanded

Profiles fastening and installation:
Check our website www.geolaminc.com

Standard length: 9 ft 10 in | 3.0 m

Or order custom lengths from:
7 ft to 19 ft 8 in | 2.15 m to 6 m

Weight: 0.57 lb/ft | 0.85 kg/m

Secondary moment I_x (cm⁴): 2.75

Secondary moment I_y (cm⁴): 6.64

Section modulus Z_{+x} (cm³): 1.81

Section modulus Z_{-x} (cm³): 2.05

Section modulus Z_{+y} (cm³): 2.56

Section modulus Z_{-y} (cm³): 2.72

Core in anodized aluminum alloy:
A6063S-T5 Serie 6000


Coefficient of Thermal Expansion (20-100°C):
23.4 μm/m/°C

Modulus of Elasticity: 68.9 GPa

Max Tensile Strength: 186 Mpa

Carbon Footprint:
WPC : 1.54 kg CO₂ /Kg
Profile : 9.005 kg CO₂ /Kg

Sanding finish and/or shading may vary between runs

Standard Colors -  Teak and Rosewood stocked in the US, no minimum.
Minimum 1,000 ft for Moleskin and Ebony.



Teak



Moleskin



Rosewood



Ebony


Non-Standard Colors - 90 day lead time - Minimum order 5,000 ft.



Ivory




Blackwood




Bilinga

Custom Colors Available - Minimum order 10,000 ft.

www.geolaminc.com
Toll free: 1-877-627-3530
info@geolaminc.com



Technical specifications, dimensions in mm		Cross section coefficient Z+x (cm ³)	1.81	Wood hybrid system WHS	Type 1.0
Weight (kg/ml)	0.85	Cross section coefficient Z-x (cm ³)	2.05	Soleo 6008	
Cross section, secondary moment Ix (cm ⁴)	2.75	Cross section coefficient Z+y (cm ³)	2.56		
Cross section, secondary moment Iy (cm ⁴)	6.40	Cross section coefficient Z-y (cm ³)	2.72		
 usa.geolam.com					